

## Product naming

<b>Model name</b>	HP LaserJet Pro MFP M26nw Printer
<b>Product number</b>	T0L50A

## What's included and accessories

<b>What's in the box</b>	HP LaserJet Pro M26nw Printer; Preinstalled HP Original Introductory Black LaserJet Toner Cartridge; Getting Started Guide, Setup poster, Support flyer, Warranty Guide; Software drivers and documentation on CD-ROM; Power cord; USB cable
--------------------------	--

## Connectivity

<b>Ports</b>	Hi-Speed USB 2.0 port; built-in Fast Ethernet 10/100Base-TX network port; built-in Wi-fi 802.11b/g/n
--------------	--

<b>Wireless capability</b>	Yes, built-in Wi-Fi 802.11b/g/n
----------------------------	---------------------------------

## Copy

<b>Copier settings</b>	Number of copies; Lighter/Darker; Reduce/Enlarge; Optimize (draft, text, mixed, picture); Paper Size
<b>Maximum number of copies</b>	Up to 99 copies
<b>Copy reduce / enlarge settings</b>	25 to 400%
<b>Copy speed (black, normal)</b>	Up to 18 cpm
<b>Copy resolution</b>	Up to 600 x 400 dpi

## Environmental

<b>Acoustic power emissions</b>	6.2 B(A)
<b>Operating humidity range</b>	30 to 70% RH
<b>Storage humidity</b>	10 to 90% RH
<b>Recommended operating temperature range (Celsius)</b>	17.5 to 25°C
<b>Recommended operating temperature range (Fahrenheit)</b>	63.5 to 77°F
<b>Storage temperature range (Celsius)</b>	-20 to 60°C
<b>Storage temperature range (Fahrenheit)</b>	-4 to 140°F
<b>Environmental specifications</b>	Mercury free

## Memory

<b>Memory, standard</b>	128 MB
-------------------------	--------

## Mobile printing capability

<b>Mobile printing services</b>	HP ePrint; Mopria
---------------------------------	-------------------

## Networking

<b>Network protocols, supported</b>	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv1, HTTP
-------------------------------------	--

## Paper handling

<b>Input capacity</b>	Up to 150 sheets
<b>Output capacity</b>	Up to 100 sheets
<b>Media sizes supported (metric)</b>	A4; A5; B5-Japanese; envelopes (ISO DL, C5, B5); 16K; postcards (JIS single and double)

<b>Media sizes supported (U.S. standard)</b>	Letter; Legal; Executive; envelopes (Com #10, Monarch #7 3/4); postcards (Standard #10)
<b>Media sizes, custom (metric)</b>	76 x 127 to 216 x 356 mm
<b>Media sizes, custom (U.S. standard)</b>	3 x 5 to 8.5 x 14 in
<b>Media types</b>	Paper (plain, LaserJet), envelopes, transparencies, labels, postcards
<b>Media weight supported (metric)</b>	60 to 163 g/m <sup>2</sup>
<b>Media weight supported (U.S. standard)</b>	16 to 43 lb

## Physical dimensions

<b>Maximum dimensions (W x D x H, metric)</b>	42 x 36.5 x 41 cm
<b>Maximum dimensions (W x D x H, U.S. standard)</b>	16.5 x 17.2 x 16.1 in
<b>Weight (metric)</b>	8.0 kg

<b>Weight (U.S. standard)</b>	17.6 lb
-------------------------------	---------

## Power

<b>Power supply type</b>	Built-in power supply
<b>Power supply</b>	Input voltage 110 to 127 VAC (+/- 12%), 60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 12%), 50/60 Hz (+/- 3 Hz)
<b>Power consumption</b>	355 watts (active printing), 2.2 watts (ready), 1.4 watts (sleep), 0.25 watts (Auto Off/Wake on USB, with wireless disabled), 0.10 watts (Auto-off/Manual-on), 0.10 (Manual Off)

## Print cartridges

<b>Number of print cartridges</b>	1 Black
<b>Replacement cartridges</b>	HP 79A Original Black LaserJet Toner Cartridge, CF279A

## Printing specifications

<b>Print technology</b>	Laser
<b>Duplex printing</b>	Manual duplex
<b>Print resolution (best)</b>	Up to 600 x 600 dpi
<b>Maximum print area (metric)</b>	209 x 349 mm
<b>Maximum print area (U.S. standard)</b>	8.2 x 13.7 in
<b>Monthly duty cycle</b>	Up to 5,000 pages
<b>Print languages</b>	PCLm/PCLmS
<b>Printer smart software features</b>	HP Auto-On/Auto-Off, HP ePrint, Mopria, Embedded Web Server

## Regulatory specifications

<b>Regulatory model number</b>	SHNGC-1505-01
--------------------------------	---------------

<b>Safety</b>	IEC 60950-1:2005 +A1:2009+A2:2013/EN60950-1:2006 +A11:2009 +A1:2010+A12:2011+A2:2013; IEC 60825-1:2007 / EN 60825-1:2007 (Class 1 Laser/LED Product), IEC 62479:2010 / EN 62479:2010, GB4943-2011
<b>Electromagnetic compatibility</b>	CISPR 22:2008 / EN 55022:2010 - Class B, EN 61000-3-2:2006 +A1:2009 +A2:2009, EN 61000-3-3:2013, EN 55024:2010, FCC Title 47 CFR, Part 15 Class B / ICES-003, Issue 6, GB9254-2008, GB17625.1-2012

## Scan

<b>Scan technology</b>	CIS
<b>Scan resolution, hardware</b>	Up to 1200 x 1200 dpi
<b>Levels of grayscale</b>	256
<b>Bit depth</b>	24-bit
<b>Maximum flatbed scan size (metric)</b>	216 x 297 mm
<b>Maximum flatbed scan size (U.S. standard)</b>	8.5 x 11.7 in



<b>Twain version</b>	Version 1.9
----------------------	-------------

## Security

<b>Security management</b>	Password-protected network embedded Web server; 802.11: WEP, WPA, WPA2; SNMPv1 community password change
----------------------------	--

## System requirements

<b>Minimum system requirements for Windows</b>	Windows 10 (32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Windows 7 (32-bit/64-bit): 1 GHz 32-bit (x86) or 64-bit (x64) processor, 1 GB RAM (32-bit) or 2 GB RAM (64-bit), 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port; Windows Vista (32-bit): 1 GHz 32-bit (x86) processor, 1 GB RAM (32-bit), 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port; Windows XP (32-bit, SP2): Pentium 233 MHz processor, 512 MB RAM, 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port; Windows Server 2003 (32-bit, SP1 or greater), Windows Server 2003 R2 (32-bit), Windows Server 2008 (32-bit, SP1 or greater), Windows Server 2008 (64-bit, SP1 or greater), Windows Server 2008 R2 (64-bit), Windows Server 2008 R2 (64-bit, SP1): 1 GHz 32-bit (x86) processor, 1 GB RAM (32-bit), 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or network port
--	---

<b>Minimum system requirements for Macintosh</b>	Mac OS X v10.11 (El Capitan), v10.10 (Yosemite), v10.9 (Mavericks): 1 GB available space, Internet access
<b>Compatible network operating systems</b>	Windows: Full software installs supported on Windows 10 (32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Windows 7 (32-bit and 64-bit), Windows Vista (32-bit and 64-bit), Windows XP (32-bit, SP2 or higher); Driver only installs supported on: Windows 2012; Windows Server 2008 (32-bit and 64-bit), Windows Server 2008 R2 (x64, SP1), Windows Server 2008 (Standard Edition), Windows Server 2008 (Enterprise Edition), Windows Server 2003 (32-bit and 64-bit, SP1 or higher), Windows XP (64-bit, SP2 and higher); Mac OS X v10.11 (El Capitan), v10.10 (Yosemite), v10.9 (Mavericks); 1 GB available hard disk space; Internet required

## Warranty

<b>Warranty</b>	One-year limited warranty
-----------------	---------------------------